EZ Slim Series Specification

Less is more !

Revolutionary slim UHD narrow pixel pitch LED display

- Super slim design - panel thickness < 38 mm/1.5 inch
- Super light weight design - a panel < 11 lbs
- Extremely user friendly - completely front install & front maintenance



- Complete installation solution package - from design to execute
- Versatile installation solutions including wall mounting, ground supporting, hanging

EZ Slim Series Specification

APPLICATION	INDOOR			
Pixel Pitch	1.2mm	1.5mm	1.8mm	2.3mm
Pixel Density(pixel/sqm)	640000	409600	284444	182044
Panel Resolution(w×h)	480*270	386*216	320*180	256*144
Panel Weight	5kg	5kg	5kg	5kg
Protection Level(front/back)	IP40	IP40	IP40	IP40
Panel Power Consumption(ave./max.)	45/150	43/145	40/135	40/120
Brightness(adjustable)	650 Nits	700 Nits	800 Nits	900 Nits
Viewing Angle(h×v)	160°/160°			
LED Type	SMD 3-in-1			
Module Size	150mm*168.75mm			
Panel Size	600mm*337.5mm			
Maintenance Method	Front			
Panel Material	Die-casting Aluminum			
Brightness/Color Calibration	Yes			
Refresh Rate	3840Hz Adjustable			
Grey Level(adjustable)	16bit adjustable			
Color Temperature	6500K			
Operating Voltage	AC100~240V(50~60Hz)			
Contrast Ratio	5000:1			
Working Humidity(rh)	10 ~ 80% No condensation			
Working Temperature	-20℃~45℃			
Life Time(hrs)	100000			
Color Uniformity	±0.0035 Cx,Cy			
Luminance Uniformity	≥97.5%			

Contact Information
EZ LED Visual Co., Ltd.
Shenzhen · Hong Kong · US · Germany
sales@ezledvisual.com
http://www.ezledvisual.com